

# Datasheet of SAW Duplexer 2520 Band25(2) for Base station


KYOCERA Part No. : SD25 1962R9UUA1

KYOCERA Corporation  
All rights reserved

### Rating

Items	Rating	Unit	Note
Operating Temperature Range	-40 to +95	deg.C	
Storage Temperature Range	-40 to +95	deg.C	
Max Input Power (Tx port)	+30	dBm	LTE 5MHz (PAR=6.95dB) 10 years @95deg.C
Tx Port Nominal Impedance	50	ohm	Unbalance
Ant. Port Nominal Impedance	50//3.3nH	ohm	Unbalance
Rx Port Nominal Impedance	50//6.2nH	ohm	Unbalance


### Dimensions




- \* : Identification logo
- 251 : Identification no.
- : Index mark of pin 1
- XXXX : Production code

Pin No.	Function
(1)	Tx
(3)	Rx
(6)	Ant.
Others	GND

### Recommendable Land Pattern



### Measurement Circuit





## Electrical Characteristics

ITEMS		Frequency Range (MHz)	Characteristics			Unit	Note	
			Min.	Typ.	Max.			
Tx to Ant	Average Insertion Loss (Over any 10MHz)	1930 - 1995	-	2.3	3.0	dB	Over any 10MHz average	
	Ripple	1930 - 1995	-	2.0	3.7	dB		
	VSWR	Tx	1930 - 1995	-	1.7	2.2	-	
		Ant	1930 - 1995	-	1.7	2.3	-	
	Attenuation		10 - 700	20	53	-	dB	
			700 - 1000	35	47	-	dB	
			1000 - 1400	30	41	-	dB	
			1400 - 1710	25	40	-	dB	
			1710 - 1780	40	44	-	dB	
			1755 - 1850	35	46	-	dB	
			1850 - 1910	50	53	-	dB	
			1910 - 1915	43	54	-	dB	Over any 5MHz average
			2025 - 2110	8	22	-	dB	
			2110 - 2300	25	44	-	dB	
			2300 - 2400	20	43	-	dB	
			2400 - 2690	30	42	-	dB	
			2690 - 3800	25	46	-	dB	
3800 - 4200	20	52	-	dB				
4200 - 5150	20	49	-	dB				
5150 - 6000	40	50	-	dB				
Ant to Rx	Average Insertion Loss (Over any 5MHz)	1850 - 1915	-	2.0	3.8	dB	Over any 5MHz Average	
	Ripple	1850 - 1915	-	1.5	2.9	dB		
	VSWR	Rx	1850 - 1915	-	1.3	2.2	-	
		Ant	1850 - 1915	-	1.4	2.4	-	
	Attenuation		0 - 700	30	53	-	dB	
			700 - 1000	40	45	-	dB	
			1000 - 1400	20	36	-	dB	
			1400 - 1600	29	34	-	dB	
			1600 - 1800	25	35	-	dB	
			1800 - 1830	15	30	-	dB	
			1930 - 1995	42	52	-	dB	Over any 5MHz average -20~+95degC
			1930 - 1995	32	52	-	dB	Over any 5MHz average -40~-20degC
			1995 - 2110	33	37	-	dB	
			2110 - 2200	20	37	-	dB	
			2200 - 2690	30	37	-	dB	
2690 - 3400			25	43	-	dB		
3400 - 3800			35	41	-	dB		
3800 - 5150	20	36	-	dB				
5150 - 6000	30	35	-	dB				
Tx to Rx	Average Isolation (over any 5MHz)	1850 - 1910	50	54	-	dB	Over any 5MHz average	
		1910 - 1915	49	59	-	dB		
		1930 - 1995	37	54	-	dB	Over any 5MHz average -20~+95degC	
		1930 - 1995	31	54	-	dB	Over any 5MHz average -40~-20degC	



### Electrical Characteristics

[Tx to Ant]





**Electrical Characteristics**

[Ant to Rx]









### Electrical Characteristics

[Tx to Rx]




### Electrical Characteristics



## Tape & Reel Specification


### [Tape]




Unit : mm

Part	Dimension
A	2.3±0.1
B	2.8±0.1
C	8.0±0.1
D	3.50±0.05
E	1.75±0.10
F	4.0±0.1
G	4.0±0.1
H	2.00±0.05
φJ	1.5±0.1
φK	1.0±0.1
R	0.3 Max
W	0.9±0.1
T	0.20±0.05

W : Dimension is depth of pockets.



### [Reel]



Unit : mm

Part	Dimension
A	178 ± 2
B	60 ± 2
C	13.0 ± 0.2
D	21.0 ± 0.8
E	2.0 ± 0.5
R	1
W	9.5 ± 1.0
T	2.0 ± 0.2

## Notice

1. Characteristics described in this datasheet are for references specifications shall be based on written documents agreed by each party.
2. Contents in this datasheet are subject to change without notice. It is recommended to confirm the latest information at the time of usage. Also, this datasheet is revised once a year. We may not be able to accept requests based on old datasheets.
3. Products in this datasheet are intended to be used in general electronic equipment such as office equipment, audio and visual equipment, communication equipment, measurement instrument and home appliances. It is absolutely recommended to consult with our sales representatives in advance upon planning to use our products in applications which require extremely high quality and reliability such as aircraft and aerospace equipment, traffic systems, safety systems, power plant and medical equipment including life maintenance systems.
4. Even though we strive for improvements of quality and reliability of products, it is requested to design with enough safety margin in equipment or systems in order not to threaten human lives directly or damage human bodies or properties by an accidental result of products.
5. It is requested to design based on guaranteed specifications for such as maximum ratings, operating voltage and operating temperature. It is not the scope of our guarantee for unsatisfactory results due to misuse or inadequate usage of products in the datasheet.
6. Operation summaries and circuit examples in this datasheet are intended to explain typical operation and usage of the product. It is recommended to perform circuit and assembly design considering surrounding conditions upon using products in this datasheet.
7. Technical information described in this datasheet is meant to explain typical operations and applications of products, and it is not intended to guarantee or license intellectual properties or other industrial rights of the third party or Kyocera.
8. Trademarks, logos and brand names used in this datasheet are owned by Kyocera or the corresponding third party.
9. Certain products in this datasheet are subject to the Foreign Exchange and Foreign Trade Control Act of Japan, and require the license from Japanese Government upon exporting the restricted products and technical information under the law. Besides, it is requested not to use products and technical information in the datasheet for the development and/or manufacture of weapons of mass destruction or other conventional weapons, nor to provide them to any third party with the possibility of having such purposes.
10. It is prohibited to reprint and reproduce a part or whole of this datasheet without permission.